Tractors PK

MF240 50HP



PERFORMANCE

Maximum engine power at 2,250 rpm 50 hp^* Maximum torque at 1,400 rpm 172 Nm Maximum PTO power at rated 44 hp^{**} engine speed

*Certified to BU AU 141a: (1971)

** Manufacturer's estimate

ENGINE

Type Diesel AD 3.1524 No. Of Cylinders 3 Injection Direct Bore 91.4mm Stroke 127.0 mm Capacity 2.5 | Compression ratio 16.5:1 Natural Aspiration Starting Aid **Thermostat** Throttle control Hand and foot Cooling Water Oil bath Air Cleaner Type Over Bonnet, air swirl Air Pre-Cleaner Fuel filter Dual, high capacity Vertical Exhaust

ELECTRICS

 Voltage
 12 V, Negative Earth

 Battery
 110 Ah

 Starter
 2.2 kW

 Alternator
 32 Amp

CLUTCH

Type Dual clutch Diameter 305 x 254 mm

TRANSMISSION

Type Sliding Spur
Number of gears & forward, 2 reverse
Road speed at 2,250 engine rpm with

12.4 / 11 - 28 rear tyrea

12.47 11 - 20 1ear tyrea			
	Gear		Speed (kph)
	Forward 1	(first low)	2.7
	Forward 2		3.9
	Forward 3		5.3
	Forward 4		7.2
	Forward 5	(first high)	10.6
	Forward 6		15.6
	Forward 7		21.3
	Forward 8		28.6
	Reverse 1	(low)	3.6
	Reverse 2	(high)	14.5

POWER TAKE OFF

Type Live
Engine speed at 240 PTO rpm 1,789 rpm
Shaft diameter 35 mm
no. Of splines 6

HYDRAULICS

Functions Draft control,
Position control,
Response control,
Constant pumping

Pump Type Reciprocating Ferguson Pump Maximum Oil Flow 16:/mix Maximum Pressure 19.2 Mpa

Max. Lift capacity with 1,415 kg lower links horizontal

Lower Links With cat. I & II interchangeable balls

FRONT AXLE

Type Box Section, Adjustable

STEERING

Steering Manual

REAR AXLE AND BRAKES

Brake Type

Actuation

Actuation

Mechanical,
Independent or locked
together

Parking Brake

Differential lock

Mechanical

Mechanical

INSTRUMENTATION

Gauges Technometer, Hourmeter, Feul level, Battery condition & Water temeprature

Warning lights Direction indicators,
Battery charge,
Headlight main beam,
Low engine oil

TYRES

Front 6.00 - 16 (6PR) Rear 12.4 / 11 - 28 (6PR)

pressure & Brake lights

TRACK ADJUSTMENT

Front 1,245 - 1,854 mm

Rear 1.321 - 1.930 mm

WEIGHTS AND DIMENSIONS

Weight

Gross Weight 1,690 kg

Dimensions

 Wheel base
 1,892 mm

 Overall Length
 3,260 mm

 Overall width (min)
 1,651 mm

Height

Over exhaust 2,145 mm
Over steering wheel 1,410 mm

Turning Circle

With brakes 5,560 mm Without brakes 6,200 mm

Ground Clearance

Under gear box 338 mm

CAPACITIES

 Fuel tank
 47.5 I

 Engine pump
 6.8 I

 Cooling system
 10.2 I

 Hydraulic system
 33.0 I

 Steering box
 0.9 I

 Oil bath air-cleaner
 0.65 I

STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

OPTIONAL EQUIPMENT

Front end weights, swinging drawber, sun Canopy.