Tractors.pk

MF260 60HP



PERFORMANCE

60 hp* Maximum engine power at 2,250 rpm Maximum torque at 1,600 rpm 212 Nm Maximum PTO power at rated 48 hp** engine speed

*Certified to BU AU 141a: (1971)

** Manufacturer's estimate

ENGINE

Type Diesel T 3, 1524 No. Of Cylinders Injection Direct Bore 91.4 mm Stroke 127 mm Capacity 2.51 Turbo Aspiration Compression Ratio 15.5:1 Starting Aid Thermostat Throttle Control Hand and foot Cooling Water Air Cleaner Type Oil Bath Air Pre-cleaner Over bonnet, air swirl Fuel Filter Dual, high capacity Exhaust Vertical Oil Cooler

ELECTRICS

Voltage 12 V. Negative Earth 110 Ah Battery Starter 2.2 kW Alternator 32 Amp.

Air Cooled, Fin type

CLUTCH

Dual Type Diameter 305 254 mm

TRANSMISSION

Type Sliding Spur 8 forward, 2 reverse Number of gears Road speed at 2.250 engine rpm with

440142 20 ----

14,9 / 13-28 [ear tyres	
Gear		Speed (kph)
Forward 1	(first low)	2.7
Forward 2		3.9
Forward 3		5.3
Forward 4		7.2
Forward 5	(first high)	10.7
Forward 6		15.6
Forward 7		21.3
Forward 8		28.7
Reverse 1	(low)	3.6
Reverse 2	(high)	14.5

POWER TAKE OFF

Type Live Engine speed at 540 PTO rpm 1,789 rpm Shaft diameter 35 mm No. Of splines

HYDRAULICS **Functions** Draft control, Position control Response control Constant pumping **Pump Type** Reciprocating Ferguson pump Maximum oil Flow 161/min Maximum Pressure 21 Mpa at normal operating temperature Max. Lift capacity with lower 2,170 kg links horizantal Lower links With Cat. I & II

interchangeable balls

STEERING

Type Box Section. Adjustable Steering Manual

REAR AXLE AND BRAKES

Axle Type Straddle with epicyclic reduction Brake Type oil immersed, multi-**Brakes Actuation** Mechanical Parking Brake Hand Lever Operated

INSTRUMENTATION

Gauges Technometer, Hourmeter, Feul leve, Battery condition & Water temprature Warning Lights Direction indicators, Electric charge Low engine oil pressure & Brake lights

TYRES Front 7.50 - 16 (6PR) Rear 14.9 / 13 - 28 (6PR)

TRACK ADJUSTMENT

Front 1,245 - 1,854 mm

Rear 1,423 - 2,134 mm

WEIGHTS AND DIMENSIONS

Weight	
Gross Weight	1,920 kg

Dimensions

Wheel base	1,892 mm
Overall Length	3,260 mm
Overall width (min)	1,890 mm

Height

Over exhaust	2,220 mn
Over steering wheel	1 490 mm

Turning Circle

With brakes	5,840 mm
Without brakes	6 580 mm

Ground Clearance

Under gear box	400 mm
Under dear box	400 1111

CAPACITIES

Fuel tank	47.51
Engine pump	6.81
Cooling system	10.2
Hydraulic system	36.01
Steering box	0.91
Oil bath air-cleaner	0.51

STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring suspension seat, Flat top fender & operator's Manual

OPTIONAL EQUIPMENT

Front end weights, swinging drawber sun Canopy.