Tractors PK

МF260 60НР



PERFORMANCE

Maximum engine power at 2,250 rpm	60 hp*
Maximum torque at 1,600 rpm	212 Nm
Maximum PTO power at rated	48 hp**
engine speed	
*Certified to BU AU 141a : (1971)	
** Manufacturer's estimate	

ENGINE

Forward 7

Forward 8

Reverse 1

Reverse 2

(low)

(high)

Туре		Diesel T 3. 1524
No. Of Cylinders	S	3
Injection		Direct
Bore		91.4 mm
Stroke		127 mm
Capacity		2.5 I
Aspiration		Turbo
Compression Ra	atio	15.5 : 1
Starting Aid		Thermostat
Throttle Control		Hand and foot
Cooling		Water
Air Cleaner Type	е	Oil Bath
Air Pre-cleaner		Over bonnet, air swirl
Fuel Filter		Dual, high capacity
Exhaust		Vertical
Oil Cooler		Air Cooled, Fin type
ELECTRICS		
Voltage		12 V. Negative Earth
Battery		110 Ah
Starter		2.2 kW
Alternator		32 Amp.
CLUTCH		
Туре		Dual
Diameter		305 254 mm
TRANSMISSION		
Туре		Sliding Spur
Number of gears	5	8 forward, 2 reverse
Road speed at 2	.250 engine rp	om with
14.9 / 13-28 rear	tyres	
Gear		Speed (kph)
Forward 1	(first low)	2.7
Forward 2		3.9
Forward 3		5.3
Forward 4		7.2
Forward 5	(first high)	10.7
Forward 6		15.6

POWER TAKE OFF

Туре	Live
Engine speed at 540 PTO rpm	1,789 rpm
Shaft diameter	35 mm
No. Of splines	6

HYDRAULICS

Front

Rear

21.3

28.7

3.6

14.5

Functions	Draft control,
	Position control
	Response control
	Constant pumping
Pump Type	Reciprocating
	Ferguson pump
Maximum oil Flow	16 I / min
Maximum Pressure	21 Mpa
	at normal operating
	temperature
Max. Lift capacity with lowe	er 2,170 kg
links horizantal	
Lower links	With Cat. I & II
	interchangeable balls

STEERING Туре Box Section, Adjustable Steering Manual **REAR AXLE AND BRAKES** Axle Type Straddle with epicyclic reduction Brake Type oil immersed, multidisc **Brakes Actuation** Mechanical Parking Brake Hand Lever Operated INSTRUMENTATION Gauges Technometer. Hourmeter, Feul leve, Battery condition & Water temprature Warning Lights Direction indicators, Electric charge Low engine oil pressure & Brake lights TYRES

7.50 - 16 (6PR)

14.9 / 13 - 28 (6PR)

TRACK ADJUSTMENT		
Front	1,245 - 1,854 mm	
Rear	1,423 - 2,134 mm	
WEIGHTS AND DIMENSI	ONS	
Weight		
Gross Weight	1,920 kg	
Dimensions		
Wheel base	1,892 mm	
Overall Length	3,260 mm	
Overall width (min)	1,890 mm	
Height		
Over exhaust	2,220 mm	
Over steering wheel	1,490 mm	
Turning Circle		
With brakes	5,840 mm	
Without brakes	6,580 mm	
Ground Clearance		
Under gear box	400 mm	
CAPACITIES		
Fuel tank	47.5	
Engine pump	6.8 I	
Cooling system	10.2	
Hydraulic system	36.0	
Steering box	0.9	
Oil bath air-cleaner	0.5	
STANDARD EQUIPMENT		
Weight frame without we	- ·	
box with set of tools, Top link, Top link end		
cat-i, Cat-I & II balls, Check chains, Spring		
suspension seat, Flat top fender &		
operator's Manual		
OPTIONAL EQUIPMENT		
Front end weights, swinging drawber sun		

ign Canopy.